

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: PRECISION CHIPPING STOPPER
PRODUCT CODE: 000000000000182627

HMIS CODES: H F R P
1 3 0 G

=====
SECTION I - MANUFACTURER IDENTIFICATION
=====

MANUFACTURER'S NAME: LAMOON BEAUTY PRODUCTS, INC
ADDRESS : 14931 CHESTNUT ST.
WESTMINSTER, CA 92683

EMERGENCY PHONE : 1-800-424-9300
INFORMATION PHONE : 1-714-892-9293

DATE PRINTED : 9/21/2007
NAME OF PREPARER : Environmental
Department

Chemtrec's EMERGENCY TELEPHONE NUMBER 1-800-424-9300 is to be used "only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals"

CHEMTREC MSDS GROUP #: 12

CHEMICAL NAME: VOLATILE SOLVENT
TRADE NAME: NAIL POLISH THINNER (TOLUENE FREE)
CHEMICAL FAMILY: OXYGENATED HYDROCARBON

=====
SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION
=====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
ETHYL ACETATE	141-78-6	76 20°C	>50%
TLV/PEL: 400 PPM			
HEPTANE	142-82-5	40 20 C	10.0% - 20.0%
TLV/PEL: 500 PPM			
* SD ALCOHOL 40B	64-17-5	44.6 20C	5.0% - 10.0%
1000 PPM (TWA) for ethyl alcohol			

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

-Components in this product have been verified as being on the TSCA Inventory and has been classified in accordance with the hazard criteria of the CPR and all information required.-

THIS PRODUCT CONTAINS NO CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR BIRTH DEFECTS AND/OR OTHER REPRODUCTIVE HARM.

=====
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS
=====

BOILING RANGE: 171°F - 210°F
VAPOR DENSITY: Heavier than air
SPECIFIC GRAVITY (H2O=1): 7.014 lb/gl
EVAPORATION RATE: (M - BUTYL ACETATE = 1): > 1.0

COATING V.O.C.: 4.89 lb/gl
SOLUBILITY IN WATER: Moderate
APPEARANCE AND ODOR: Clear solution with ester odor.
MATERIAL V.O.C.: 4.86 lb/gl

=====
SECTION IV - FIRE AND EXPLOSION HAZARD DATA
=====

FLASH POINT: 24°F
METHOD USED: TCC

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.5 UPPER: 19.0

EXTINGUISHING MEDIA: Water is the most effective fire extinguishing medium for Nitrocellulose. It is recommended to be used in large volume. Dry chemical, CO2 or a universal type foam could be used to extinguish small fires.

SPECIAL FIREFIGHTING PROCEDURES

High heat on drums of this material will cause the evaporation of solvent contents, resulting in an increase in pressure causing the release of the drum lid or even the drum explosion. Do not approach fires involving this material before cooling the drums in the fire to decrease the chance of drum lid release or drum explosion. Fight fires from a safe distance.

Self-contained breathing apparatus should be used, to eliminate or minimize breathing vapor, fumes or gases released from the decomposed product. Use water to keep fire-exposed containers cool. Water spray may be used to flush spills away from exposures. Avoid spreading burning material with water.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Handle as flammable liquid. Vapors form an explosive mixture in air between the upper and lower explosive limits which can be ignited by many sources such as pilot lights, open flames, electrical motors and switches

===== SECTION V - REACTIVITY DATA =====

STABILITY: Stable

CONDITIONS TO AVOID

Flame, electric spark, static, and heat.

INCOMPATIBILITY (MATERIALS TO AVOID)

This product is incompatible with strong acids or bases and oxidizers.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide, and nitrogen oxide. Under some conditions, methane, irritating aldehydes and carboxylic acids and hydrogen cyanide may be formed.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Breathing high concentrations of vapors or mists may cause irritation of the nose and throat. Signs of nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EYE: This product may cause eye irritation. Direct contact with this material or exposure to its vapors or mists (greater than approximately 1000 ppm) may cause burning, tearing, redness, and swelling.

SKIN: This product may cause skin irritation. Prolonged or repeated exposure to this material may cause redness and burning, drying and cracking of and dermatitis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Ingestion of excessive quantities may cause irritation of the digestive tract. Sign of nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

M A T E R I A L S A F E T Y D A T A S H E E T

HEALTH HAZARDS (ACUTE AND CHRONIC)

No ingredient present in this product is identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA. Reports have associated repeated and prolonged occupational overexposure to solvent present in this product with permanent brain and nervous system damage (sometimes referred to as solvent or painter's syndrome). Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

CARCINOGENICITY: NTP CARCINOGEN:No IARC MONOGRAPHS: No OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Respiratory symptoms associated with pre-existing lung disorders (e.g., asthma-like conditions) may be aggravated by exposure to the vapors of this material. Persons with pre-existing skin disorders may be more susceptible to the effects of this material.

EMERGENCY AND FIRST AID PROCEDURES

Inhalation - Move person to fresh air. If breathing stops, apply artificial respiration and seek immediate medical attention.
Eye contact - flush with large quantities of water for 15 minutes, lifting upper and lower lids. Seek medical attention.
Skin contact - Wash thoroughly soap and water and seek medical attention.
Ingestion - Do not induce vomiting! Vomiting can cause chemical pneumonitis and pulmonary edema. Contact physician immediately.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Highway or railway spills call chemtrec (800) 424-9300 cont. U.S. Collect (202) 483-7616 from Alaska and Hawaii.

Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone number: 800-424-8802) in case if the spill is in excess of EPA reportable quantity.

WASTE DISPOSAL METHOD

Dispose of product in accordance with local, county, state, and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Use non-sparking utensils when handling this material. Keep containers, tightly closed, cool, dry and away from sources of ignition.

OTHER PRECAUTIONS

Smoking in area where this material is used should be strictly prohibited. Use with adequate ventilation. If normal ventilation is not adequate use with NIOSH approved respirator or exhaust fan.

===== SECTION VIII - CONTROL MEASURES =====

PREVENTATIVE MEASURES:

Keep containers and storage containers closed when not in use. Do not store near heat, sparks, flame, or strong oxidants. While transferring this material the containers used in this process has to be effectively grounded (ultimately to an earth ground) to prevent fire or explosion risk from static accumulation in accordance with the National Fire Protection Association standard for petroleum products.

RESPIRATORY PROTECTION

When vapor concentration exceed the established exposure limits respiratory protection is necessary. Depending on the airbourne concentration, use a respirator or gas mask with appropriate cartridges and canisters (NIOSH approved organic vapor) or supplied air equipment.

VENTILATION

The ventilation system should be designed to be able to maintain airborne conceateations below the established exposure limits. If the current ventilation is not adequate to maintain this level, additional ventilation or exhaust systems may be required. Use explosion proof equipment.

PROTECTIVE GLOVES

The use of gloves impermeable to the specific material handled is advised to prevent skin contact and possible irritation.

EYE PROTECTION

Safety glasses with side shields (or goggles) are recommended for any type of industrial chemical handling.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

The use of gloves impermeable to the specific material handled is advised to prevent skin contact and possible irritation. Use splash goggles (NIOSH approved) to safeguard against potential eye contact, irritation or injury.

WORK/HYGIENIC PRACTICES

Minimize breathing vapor or mist. Avoid prolonged or repeated contact with skin. Maintain a source of clean water to be available in work area for flushing eyes and skin. Remove contaminated clothing; launder or dry-clean before use. Remove contaminated shoes and thoroughly clean and dry before reuse. Cleanse skin thoroughly after contact, before breaks and meals, and at end of work period. Product is readily removed from skin by waterless hand cleaners or solvents (acetone or esters) followed by washing with soap and water. Impervious clothing should be worn as needed.

=====**SECTION IX - SHIPPING INFORMATION**=====

Proper Shipping Name: Paint related material
DOT Hazard Class: 3 (Flammable Liquid)
Packaging Group: PG II
UN ID Number: UN1263

=====**SECTION X - DISCLAIMER**=====

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Lamoon to be accurate. As with all chemicals, KEEP AWAY FROM CHILDREN AND ANIMALS. FOR TOPICAL USE ONLY.